

# LSI ABOLITE DEEP BOWL



**FINISH** - Available in either Architectural Textured or High Gloss finish.

**LAMP OPTIONS** - Designed to accommodate Incandescent, Compact Fluorescent, and High Intensity Discharge lamps. CFL and HID lamps available – order separately; Incandescent lamps by other.


**REFLECTOR** - Heavy-duty, spun galvanized steel construction.

**MOUNTING** - Cast aluminum hub tapped for 3/4" NPT conduit. Available factory pre-wired with 96" leads or white or black cord set and canopies. Cord sets listed for damp locations only.

**SOCKETS** - Incandescent (rated 660 Watt/600 Volt) and HID fixtures (4KV pulse rated) are medium base porcelain. Compact Fluorescent sockets feature smart push-pull thermoplastic design for ease of lamping.

**BALLAST** - CFL and HID require a Wall, Ceiling, or Remote Ballast. See Accessories page.

## DIMENSIONS



Also available in LED



**ARRA**  
Funding Compliant

Fixture	Height (A)	Diameter (B)	Neck (C)	Weight (lbs./kg)
BD 200	11" (279mm)	10" (254mm)	4-3/4" (121mm)	2.5 (1.1kg)
BD 300	12" (305mm)	13" (330mm)	4-3/4" (121mm)	3.2 (1.45kg)

TYPICAL ORDER EXAMPLE: **BD 200 INC 120 MSV CA120WHT G6**

Luminaire Prefix	Lamp Wattage	Light Source	Line Voltage	Finish	Mounting	Factory Installed Options	Field Installed Accessories
BD 200 BD 300	(200 Watt Max.) (300 Watt Max.)	INC - Incandescent	120	MSV - Metallic Silver GWT - Gloss White GBK - Gloss Black GRD - Gloss Red GPT - Textured Graphite RUS - Textured Rust SVG - Satin Verde Green SCP - Satin Copper STQ - Satin Turquoise	LDS96WL - Prewired leads. For use with stem or bracket mounting in wet or indoor locations. CA120WHT - 10' prewired white cord set and canopy <sup>1</sup> CA120BLK - 10' prewired black cord set and canopy <sup>1</sup> CA120WHTS - 10' prewired white cord set and canopy with SWAG option <sup>1</sup> CA120BLKS - 10' prewired black cord set and canopy with SWAG option <sup>1</sup> CS120 5WHT - 10' prewired white 5-conductor cord set for use with CFL fixtures <sup>2</sup> CS120 5BLK - 10' prewired black 5-conductor cord set for use with CFL fixtures <sup>2</sup>	G6 - Globe <sup>3</sup> PG3 - Globe <sup>3</sup>	Ball Aligners Decorative Aligners Gooseneck & Wall Brackets Poles & Pole Brackets Stems Wire Guards Remote Ballasts
	26/32/42	CFL - Compact Fluorescent (Globe option required)	UE				
	50 70 100	MH - Metal Halide (PG3 Globe option required)	120 277				
	50 70 100	MP - Metal Halide (for use in open optics in indoor applications only)					

1- For indoor applications only. Order with incandescent and HID fixtures.

2- The 5-Wire cord sets do not include canopy. Order the SMB 26/32/42/ CFL UE GWT decorative canopy/ballast separately. For indoor applications only.

3- For wattage and size restrictions, see Abolite Globes in accessories section.



Project Name \_\_\_\_\_ Fixture Type \_\_\_\_\_  
Catalog # \_\_\_\_\_