

ABOLITE RLM STANDARD DOME



THE PERFECT FUSION OF FORM AND FUNCTION

*The professional's choice for  
downward lighting in ambient  
and accent applications.*




Abolite

# ABOLITE RLM STANDARD DOME

A CLASSIC RLM DESIGN THAT FEATURES ELEGANCE AND TIMELESS SIMPLICITY

The Abolite Standard Dome (RD) is the professional's choice when it comes to general ambient, task ambient or simple decorative lighting. Semi-shielding of lamps and/or globes directs the majority of light downward. This makes the RD a great choice for ambient and accent applications, and allows the designer to deal with scale of the area to be lighted and various mounting heights.

- Compact profile with 3/4" threaded entry
- Mounting accomplished with rigid 3/4" conduit, or a variety of brackets, goosenecks and cord sets
- Four sizes ranging from 12" to 18" in diameter
- Lamps available
  - Compact Fluorescent from 13 to 42 watts  
26/32/42 Watt requires use of separate Remote Ballast and is available with LDS96 WL mounting only
  - High-Intensity Discharge from 50 to 175 watts requires use of separate Remote Ballast
  - Incandescent up to 300 watts



U.L. Listed for wet locations

Fixture	Height (A)	Diameter (B)	Neck (C)	Weight (lbs.)
RD 100	8-1/4"	12"	4-1/2"	2.5
RD 150	9-1/2"	14"	4-1/2"	3.0
RD 200	10"	16"	4-1/2"	3.5
RD 300	11"	18"	5"	4.0



# Abolite

10000 Alliance Road ♦ Cincinnati, Ohio 45242 ♦ (513)793-3200 ♦ FAX (513)793-0147 ♦ [www.lsi-industries.com](http://www.lsi-industries.com)