

LSI LED XSL2 & XSPS

Soffit Lighting

LSI offers two high performance LED soffit fixtures for recessed downlighting applications such as soffits, canopies and drive-thrus. Both deliver smooth, uniform illumination to help pedestrians and drivers navigate effectively. Both feature 5000K (cool white) color temperature.



XSPS Low Profile LED Soffit Fixture

Ideal for Lower Lumen Packages in Shallow Plenums

XSL2 LED Soffit Fixture

Ideal for More Robust Requirements

Overall Dimensions	13 1/4" square	18" square
Fixture Depth	5 11/16"	8 1/4"
Installation Clearance	8"	12"
Performance	Super Saver (SS) 4,541 lms @ 43W; 104 lpw High Output (HO) 5,631 lms @ 59W, 96 lpw	Super Saver (SS) 5,752 lms @ 60W, 96 lpw High Output (HO) 6,751 lms @ 87W, 78 lpw
Dimming	0-10v dimmable drivers supplied as standard in SS & HO	0-10v dimmable drivers supplied as standard in HO only
Lens	Diffused	Clear and Diffused
Mounting	Direct	Direct and Channel
Distribution	Symmetric	Symmetric and Type 5A
Shipping Weight	6 lbs.	14 lbs.

