

RLM ANGLED REFLECTOR



THE PERFECT FUSION OF FORM AND FUNCTION

Combining a nostalgic look with today's lamp sources for effective signage illumination.


lsi
Lighting Solutions *plus*

RLM ANGLED REFLECTOR

CAST THE PERFECT HIGHLIGHT ON SIGNS, PRODUCT DISPLAYS, AND KEY ARCHITECTURAL FEATURES

Effective signage illumination is the primary objective of the Abolite Angled Reflector (AD). While definitely a nostalgic luminaire, combining it with today's lamp sources provides the lighting designer with a major tool for addressing both illumination levels and energy requirements. By mounting the AD in combination with the A-style gooseneck on four foot centers, both interior and exterior signage can be illuminated with confidence.

- Compact profile with 3/4" threaded entry
- Mounting accomplished with rigid 3/4" conduit, or a variety of brackets and goosenecks
- Three sizes ranging from 7" to 11" in diameter make the AD a great choice when directional lighting is needed
- Lamps available
 - Compact Fluorescent from 13 to 42 watts
26/32/42 Watt requires use of separate Remote Ballast
 - High-Intensity Discharge from 50 to 100 watts requires use of separate Remote Ballast
 - Incandescent up to 200 watts



U.L. Listed for wet locations.

Fixture Prefix	Height (A)	Diameter (B)	Neck (C)	Weight (lbs.)
AD 100	10"	7"	5"	2.0
AD 150	11-1/2"	9"	5-1/4"	2.0
AD 200	13-1/2"	11"	5-1/2"	2.5

Fixture Prefix	Rated Wattage	Light Source	Line Voltage	Reflector Color	Mounting	Factory-Installed Options	Field-Installed Accessories
AD 100 AD 150 AD 200	100 150 200	INC - Incandescent	120	GAL - Galvanized PNA - Painted Natural Aluminum GWT - Gloss White GBK - Gloss Black GRD - Gloss Red GGN - Gloss Green RUS - Textured Rust GPT - Textured Graphite VGN - Textured Verdigris	LDS96 WL - Factory prewired 8' leads for use with stem or bracket mounting in wet or indoor locations.	G6 - Globe* PG3 - Globe*	Ball Aligners Ceiling Canopies
AD 200	13 26/32/42	CFL - Compact Fluorescent (Globe option required)	UE - Universal Electronic (120-277V 50/60 Hz) 347V		Not available with cord sets		Gooseneck & Wall Brackets Poles & Pole Brackets Stems Wire Guards
AD 200	50 70 100	MH - Metal Halide (Globe option required) MP - Metal Halide** (for use in open RLMs)	120				Remote Ballasts

AD200 100 MH UE GBK LDS96 WL PG3 X

* Not available with AD 100 or AD 150. G6 not for use with Metal Halide
** MP lamps approved for Indoor use only



THE POWER OF IMAGE

LSI LIGHTING SOLUTIONS PLUS

10000 Alliance Road ♦ Cincinnati, Ohio 45242 ♦ (513)793-3200 ♦ FAX (513)793-0147 ♦ www.lsi-industries.com