

COURTSIDER® XL


LUMINAIRE ORDERING INFORMATION



TYPICAL ORDER EXAMPLE: **CXLS FT 1000 MH F MT BLK**

Luminaire Prefix	Distribution	Lamp Wattage	Light Source	Lens	Line Voltage	Finish
CXLS	FT - Forward Throw 3 - Type III ¹	1000 875 750	MH - Metal Halide 1000 Watt PSMH - Pulse-Start Metal Halide 750, 875 Watt	F - Flat Clear Tempered Glass	MT - Multi-Tap ² 480 220/240V 50HZ ³	BLK - Black GRN - Green BRZ - Bronze PLP - Platinum Plating BUF - Buff WHT - White GPT - Graphite MSV - Metallic Silver

ACCESSORY ORDERING INFORMATION (Accessories are field installed)	
Description	Order Number
HSS - House Side Shield ⁴	122521BLK+
+Black only	



House Side Shield (HSS)

FOOTNOTES:

- 1 - The Type III (3) reflector is supplied on fixtures for the Quad 90 assembly only
- 2 - **MT - Multi Tap** consists of 120V, 208V, 240V and 277V and is prepared for highest voltage. Alternate voltages will require field adjustment.
- 3 - For international applications where 50hz power is standard (e.g. Europe & Asia).
- 4 - Under normal use, the Courtsider XL fixture produces acceptable light cutoff. For highly sensitive applications, the optional external rear cutoff shield is available.

ELECTRICAL REQUIREMENTS			
	1000W	875W	750W
120V	9.2 amps	7.8 amps	6.8 amps
208V	5.3 amps	4.5 amps	3.9 amps
240V	4.6 amps	3.9 amps	3.4 amps
277V	4 amps	3.4 amps	2.9 amps
347V	3.1 amps	2.7 amps	2.3 amps
480V	2.3 amps	2 amps	1.7 amps

DISCOUNT



Project Name _____ Fixture Type _____
 Catalog # _____