

LED DOME WRAP - SURFACE / PENDANT MOUNT - DW



PRODUCT HIGHLIGHTS

- Rounded Lens for unique appearance.
- Flexible lens allows for easy access to install and service.
- Driver cover held in place with quarter turn fasteners for easy access.
- Small size allows for installation in small spaces.

LEDs - Use of closely-spaced medium-power, high-brightness chips minimizes pixelation and provides uniform lens luminance. Available in Cool White (5000K), Neutral White (4000K) and Warm White (3500K) color temperatures. CRI >= 80 (CW > 70). LM-80 reports available.

CONSTRUCTION - Fixture housing, lampholder brackets, and sections and reflector constructed of code-gauge die-formed steel.

LENS - Frosted, acrylic lens, .100 thick.

ELECTRICAL - Universal voltage (120-277 Vac) input, 50/60 Hz. Power factor > 0.9, THD < 20%, in-rush current < 15 Amps.



DRIVER - High-performance isolated driver features over-voltage, over-current and short-circuit (with auto-recovery) protection. Driver module is sealed to IP66 protection levels, with a Class A sound rating. 0-10V dimming standard.

FINISH - All metal parts painted after fabrication following treatment with phosphate rust inhibitor. Finish coating of housing reflecting surfaces is with white, high reflectance (minimum 92%) polyester powder.

WARRANTY - Limited 5-year warranty.

LISTING - UL Listed to U.S. and Canadian safety standards. Suitable for damp locations. IBEW Union made in the U.S.A. For a list of the specific products in this series that are DLC listed, please consult the LED Lighting section of our website or the Design Lights website at www.designlights.org.

DIMENSIONS



LIGHT OUTPUT - LED DW				
	WW	NW	CW	Watts
SS	5295	5220	5865	44
HO	6360	6265	7100	58

LED Chips are frequently updated therefore values may increase.

This product, or selected versions of this product, meet the standards listed below. Please consult factory for your specific requirements.



ORDERING INFORMATION

TYPICAL ORDER EXAMPLE: **DW LED SS CW UE EM**

Prefix	Light Source	Drive Current	Color Temperature	Voltage	Options
DW	LED	SS - Super Saver HO - High Output	CW - Cool White (5000K) NW - Neutral White (4000K) WW - Warm White (3500K)	UE - Universal Electronic (120-277V) 347-347V	EM - Emergency Pack BOR EOR } Row Mounting Available MOR } Consult Factory SD50 - Step Dimming to 50%

ACCESSORY ORDERING INFORMATION (Accessories are field installed)	
Description	Order Number
Pendant Mount Kit (3/8" IP Stems)	PMK
3" Chain & Large V-hook	CHSIMX3
5" Chain & Large V-hook	CHSIMX5



Project Name _____ Fixture Type _____
Catalog # _____

02/04/16
© 2015
LSI INDUSTRIES INC.