

Catalog # :

Project :

Prepared By :

Date :



## MICRO ADJUSTABLE LED WET LOCATION EMERGENCY LIGHT (EAW)



### Features & Specifications

#### Optical System

- Dual Micro Adjustable 1.4 watt LED Heads
- Optically Clear Injection Molded Polycarbonate Lens
- 99 Lumens per head

#### Electrical

- Standard Dual voltage (120/277 Vac) Input 50/60 Hz
- Sealed, maintenance-free nickel-cadmium battery provides 90 minutes of emergency power
- Typical LED life >10 years
- Provided with test switch and AC-On indicator
- Operating temperature: 0°C to 40°C (32°F to 104°F)
- UL 924 listed for damp location

#### Construction

- White Injection-molded high-impact rated thermoplastic housing
- UV-stabilized, UL94 V-0 flame rated housing
- Snap together design for quick and easy installation
- Option of wall or ceiling mount

#### Installation

- Universal J-box pattern knock-out
- Snap-together construction for speedy installation
- Universal mounting plate with quick-connect feature



#### Warranty

- LSI LED Fixtures carry a 5-year warranty.

#### Listings

- UL924 Listed for Damp Location NFPA 101 and NFPA 70 OSHA
- ADA Compliant
- NFPA 101
- NFPA 70-NEC
- OSHA

### Product Dimensions



### Ordering Guide

TYPICAL ORDER EXAMPLE: **EAW LED UNV WHT**

Catalog Number	Description
EAW LED UNV WHT	LED Adjustable Head UL Wet Location Emergency Light, Dual Voltage 120/277V, White

