

Catalog # :	Project :
Prepared By :	Date :



# LED WET LOCATION EMERGENCY LIGHT (EWL)



## Features & Specifications

### Optical System

- Dual fully Adjustable 15 LED Lamp Heads
- Adjustable Square Head LED Emergency Light

### Electrical

- Standard Dual voltage (120/277 Vac) Input 60 Hz
- Sealed, maintenance-free nickel-cadmium battery provides 90 minutes of emergency power
- Typical LED life >10 years
- Provided with test switch and AC-On indicator
- Operating temperature: 10°C to 40°C (50°F to 104°F)
- UL 924 listed for damp location
- Optional Remote-Capacity version offers up to an additional 4.4 Watts for 90 minutes

### Construction

- Off-White Injection-molded high-impact rated and corrosion resistant polycarbonate housing
- Sealed and Gasketed Housing
- Single pack shipping weight in carton: 7.5 lbs.
- Master carton quantity: 4pcs

### Installation

- Quick Installation
- External mounting brackets provided for ease of installation

### Warranty

- Five full year warranty on electronics/battery and unit.

### Listings

- UL924 Listed for Damp Location NFPA 101 and NFPA 70 OSHA
- ADA Compliant
- NFPA 101
- NFPA 70-NEC
- OSHA

## Product Dimensions

## Ordering Guide

TYPICAL ORDER EXAMPLE: **EWL LED UNV WHT**

Catalog Number	Description
EWL LED UNV WHT	LED Wet Location Emergency Light, Dual Voltage 120/277V, White

