

CAST ALUMINUM LED EXIT W/ 8" LETTERS - NYC MODEL

EXC

FEATURES

- 8" Letters Meet NYC Requirements

HOUSING

- Enclosure, Face Plate, Back Plate & Canopy Constructed of Precision Die Cast Aluminum that is Damp Location Rated
- Universal Housing Design Includes 2nd Face Plate and Canopy
- 8" Letters for NYC Meet NYC Requirements
- Knock-out Style Chevron Arrows
- Standard Finishes are White, Black, or Brushed Aluminum
- Fixture may be built to comply with the ARRA Act of 2009 and Buy American Provisions, consult factory.

ILLUMINATION

- L.E.D. source - available in long life, high output red or green
- Low Energy consumption
- Fully Illuminated 8 Inch Letter with 1" Stroke

ELECTRONICS

- 120/277 Dual Voltage with Test Button and LED AC/DC Indicator Light
- Overload & Short Circuit Protection
- Voltage Surge & Brown-out Protection
- Solid State Constant Current Charger with over-charge protection

BATTERY

- 6 volt Ni-Cad Battery on Standard Unit

MOUNTING

- Universal Mount with Canopy
- Universal J-Box Mounting Pattern

CODE CONFORMANCE & STANDARDS

- UL 924
- N.E.C.
- N.F.P.A. Life Safety Code 101
- ETL Listed 90 min. Run Time/24 Hour Recharge Time



EXIT SIGN

HEIGHT = 10-1/2"
WIDTH = 15-1/2"
DEPTH = 2"

Wire guard available. Order separately.
 See wire guard chart in Accessories section.

ORDERING INFORMATION

TYPICAL ORDER EXAMPLE: **EXC R 8 U LB BL SD2**

Prefix	Letter Color	Character Size	Number of Faces	Battery	Housing / Face	Options
EXC - Exit Sign	R - Red	8 = 8"	U-Universal (includes 2 face plates and mounting canopy)	LB-Less Battery WB-With Battery	BL-Black w/Aluminum Face BB-Black w/Black Face WW-White w/White Face BA-Brushed Aluminum w/Alumi. Face WH-White w/Aluminum Face	US - Meets Buy American Requirements



Project Name _____ Fixture Type _____
 Catalog # _____

10/09/15
 © 2015
 LSI INDUSTRIES INC.